

QMTS2.E55656

Polymeric Materials - Filamen-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

Material Dsg	Color	Build Up		R.T.I		H W I	H A I	H V T R	C T I	Meets 746E DSR
		Min Thk (mm)	Flame Class	Elec (°C)	Mech (°C)					

Vulcanized fiber, furnished as sheets or rolls.

HB-77	ALL	0.71	HB	115	110	4	0	-	-	-
		1.57	HB	115	110	3	0	-	0	-
K-57	ALL	0.74	HB	-	-	-	-	-	-	-
		1.60	HB	-	-	-	-	-	-	-
NF-77(B)	BK	0.25	V-0	-	-	0	0	-	-	-
		0.38	V-0	-	-	0	0	-	-	-
		0.80	V-0	-	-	0	0	-	-	-
		1.60	V-0	-	-	0	0	-	2	-
NF-77(N)	GY	0.25	V-0	-	-	0	0	-	-	-
		0.38	V-0	-	-	0	0	-	-	-
		0.80	V-0	-	-	0	0	-	-	-
		1.60	V-0	-	-	0	0	-	1	-
NF-77(R)	BN	0.25	V-0	90	90	1	3	-	-	-
		0.80	V-0	90	90	1	3	-	-	-
		1.60	V-0	90	90	1	4	-	2	-
RK-76	GN	0.74	HB	-	-	-	-	-	-	-
		1.60	HB	-	-	-	-	-	-	-
RNF-77	ALL	0.25	V-0	90	90	-	-	-	1	-
		0.80	V-0	90	90	2	0	-	1	-
		1.60	V-1	90	90	1	0	-	1	-
	NC,RD,WT	1.60	V-0	90	90	1	0	-	1	-

Paper phenolic vulcanized fiber, furnished sa sheets or rolls.

NFL	NC	0.18	V-0	-	-	-	-	-	-	-
		0.27	V-0	-	-	-	-	-	-	-
		0.91	V-0	-	-	-	-	-	-	-
		1.61	V-0	-	-	-	-	-	-	-

Polyurethane Coated Paperboard Vulcanized fiber, furnished sa sheets or rolls.

RK-76(S)	NC,GN,RD	0.80	HB	-	-	-	-	-	-	-
		1.60	HB	-	-	-	-	-	-	-